



S 88 G31T+PS

## **Product codes:**

Reference: 13471.01

# **Product short description:**

3" Self-priming centrifugal pump in cast iron with mechanical seal, grease-lubricated, non return valve and 15 kW electric motor close coupled

+PS automatic lubricator for mechanical seal

# **Product features:**

# **Main Features**

Pump series: S 88

Pump Flow Rate: max 95 m<sup>3</sup>/h (1580 l/min)

Pump head with 50 Hz grid frequency:  $max\ 50\ m$ 

Max. Solids Handling: 35 mm

Self-priming: ★★★★

Heavy-duty:  $\star\star\star$ 

Construction: Close Coupled

## **Pump**

Type of Pump: Self-priming centrifugal pump

Suction port: 3"

Discharge port: 3"

Type of ports: Female Thread BSP

Type of self-priming: Wet-prime

Inspection cover for the impeller: Yes

Filling port: Yes



**Drain Port:** Yes

Plug for Vacumeter: Option

Plug for the Manometer: Option

Material of casing: Cast iron

Material of impeller: Ductile Cast-iron

Material of wear plate: Steel

Material of shaft: Stainless steel AISI420

Material of non-return valve: NBR (Nitrile)

Shaft sealing: YCV Mechanical Seal with Grease Lubrication in SiC/SiO<sub>2</sub>/FKM (Viton®) on Stainless Steel

Sleeve

#### **Drive**

Type of drive unit: Three-Phase Electric Motor

Efficiency class: IE1, S6-75%

Rated Power: 15 kW (20 HP)

Maximal Rotation: 2900 rpm (50 Hz)

Rated voltage:  $400~V~\pm10\%~@~50~Hz$ ,  $690~V~\pm10\%~@~50~Hz$ 

Protection: 32 Amp (380-480 V), 19 Amp (660-725 V)

Cooling method: IC411- TEFC

Protection degree: IP55

Insulation class: F

### **Performance data**

Typical application: waste water with solids in suspension, non-corrosive

Product temperature: max. 60 °C

Ambient temperature: max. 40  $^{\circ}\text{C}$ 

Density: up to 1, 1 kg/dm³, for higher values you need an oversized motor

Viscosity: up to 5 mm<sup>2</sup>s (cSt), for higher values you need an oversized motor

Max vacuum with water: max 8 m (9, 5 m for 10 min)

Max vacuum with air: max 8, 5 m

### **Additional Features**

Setup position: Horizontal

Coupling: One shaft solution without any coupling

Paint: RAL6011 Reseda green

External Dimensions (L x W x H): 771 x 327 x 412 mm

Net Weight: 132 kg

## **Product gallery:**





