



S 60+50 G31T+F+PS

Product codes:

Reference: 15344.03

Product short description:

- 2" Self-priming centrifugal pump in cast iron with mechanical seal, grease-lubricated, non return valve and 4 kW electric motor close coupled
- +F flange coupling according DIN. PN16
- +PS automatic lubricator for mechanical seal

Product features:

Main Features

Pump series: S60+50

Pump Flow Rate: max 40 m³/h (655 l/min)

Pump head with 50 Hz grid frequency: max 36 m

Max. Solids Handling: 24 mm

Self-priming: $\star\star\star\star$ Heavy-duty: $\star\star\star\star$

Construction: Close Coupled

Pump

Type of Pump: Self-priming centrifugal pump

Suction port: DN50

Discharge port: DN50

Type of ports: DIN PN16 flange (compatible), ANSI 150lb flange

Type of self-priming: Wet-prime



Filling port: Yes

Drain Port: Yes

Plug for Vacumeter: Yes

Plug for the Manometer: Yes

Material of casing: Cast iron

Material of impeller: Cast iron

Material of wear plate: Steel

Material of shaft: Stainless steel AISI316

Material of non-return valve: NBR (Nitrile)

Shaft sealing: YCV Mechanical Seal with Grease Lubrication in SiC/SiO₂/FKM (Viton®) on Stainless Steel

Sleeve

Drive

Type of drive unit: Three-Phase Electric Motor

Drive Manufacturer: Victor Pumps

Efficiency class: IE3

Rated Power: 4 kW

Maximal Rotation: 2900 rpm (50 Hz)

Rated voltage: 400 V $\pm 10\%$ @ 50 Hz, 230 V $\pm 10\%$ @ 50 Hz

Protection: 12 Amp (380-480 V), 18 Amp (220-277 V)

Cooling method: IC411- TEFC

Protection degree: IP55

Insulation class: F

Performance data

Typical application: waste water with solids in suspension, non-corrosive

Product temperature: max. 60 $^{\circ}\text{C}$

Ambient temperature: max. 40 °C

Density: up to 1, 1 kg/dm³, for higher values you need an oversized motor

Viscosity: up to 1 mm²s (cSt), for higher values you need an oversized motor

Max vacuum with water: max 8 m (9, 5 m for 10 min)

Max vacuum with air: max 8, 5 m

Additional Features

Setup position: Horizontal

Coupling: One shaft solution without any coupling

Paint: RAL6011 Reseda green

External Dimensions (L x W x H): 622 x 275 x 399 mm

Net Weight: 81 kg





