

S 63 G31T+F



# **Product codes:**

Reference: 15320.02

# **Product short description:**

2" Self-priming centrifugal pump in cast iron with mechanical seal, grease-lubricated, non return valve and 7,5 kW electric motor close coupled

+F flange coupling according DIN. PN16

# **Product features:**

# **Main Features**

Pump series: S 63

Pump Flow Rate: max 45 m<sup>3</sup>/h (750 l/min)

Pump head with 50 Hz grid frequency:  $\max 50 \text{ m}$ 

Max. Solids Handling: 22 mm

Self-priming: ★★★★
Heavy-duty: ★★☆☆

Construction: Close Coupled

### **Pump**

Type of Pump: Self-priming centrifugal pump

Suction port: DN50

Discharge port: DN50

Type of ports: DIN PN16 flange (compatible), ANSI 150lb flange

Type of self-priming: Wet-prime

Inspection cover for the impeller: Yes

Filling port: Yes



**Drain Port:** Yes

Plug for Vacumeter: Yes

Plug for the Manometer: Yes

Material of casing: Cast iron

Material of impeller: Cast iron

Material of wear plate: Steel

Material of shaft: Stainless steel AISI316

Material of non-return valve: NBR (Nitrile)

Shaft sealing: YCV Mechanical Seal with Grease Lubrication in SiC/SiO<sub>2</sub>/FKM (Viton®) on Stainless Steel

Sleeve

#### **Drive**

Type of drive unit: Three-Phase Electric Motor

**Drive Manufacturer: Victor Pumps** 

Efficiency class: IE3

Rated Power: 7, 5 kW (10 HP)

. . . .

Maximal Rotation: 2900 rpm (50 Hz)

Rated voltage: 400 V  $\pm 10\%$  @ 50 Hz, 690 V  $\pm 10\%$  @ 50 Hz

Protection: 16 Amp (380-480 V), 11 Amp (660-725 V)

Cooling method: IC411- TEFC

Protection degree: IP55

Insulation class: F

# **Performance data**

Typical application: waste water with solids in suspension, non-corrosive

Product temperature: max. 60 °C

Ambient temperature: max. 40 °C

Density: up to 1, 1 kg/dm³, for higher values you need an oversized motor

Viscosity: up to 30 mm<sup>2</sup>s (cSt), for higher values you need an oversized motor

Max vacuum with water: max 8 m (9, 5 m for 10 min)

Max vacuum with air: max 8, 5 m

# **Additional Features**

Setup position: Horizontal

Coupling: One shaft solution without any coupling

Paint: RAL6011 Reseda green

External Dimensions (L x W x H): 642 x 331 x 405 mm

Net Weight: 77 kg

# **Product gallery:**

















