



S 40 G31BBT+PS

#### **Product codes:**

Reference: 11100.41

## **Product short description:**

 $1\frac{1}{2}$ " Self-priming centrifugal pump in cast iron with mechanical seal, grease-lubricated, non return valve and 1,1 kW electric motor Bi-Block (B5 standard motor flange-mounted on the pump bearing bracket) +**PS automatic lubricator for mechanical seal** 

## **Product features:**

### **Main Features**

Pump series: S 40

Pump Flow Rate: max 22 m<sup>3</sup>/h (360 l/min)

Pump head with 50 Hz grid frequency: max  $15\ \text{m}$ 

Max. Solids Handling: 20 mm

Self-priming: ★★★☆☆

Heavy-duty: ★★★★

Construction: Bi-Block

#### **Pump**

Type of Pump: Self-priming centrifugal pump

Pump manufacturer: Victor Pumps

Suction port:  $1\frac{1}{2}$ "

Discharge port: 1½"

Type of ports: Female Thread BSP



Type of self-priming: Wet-prime

Inspection cover for the impeller: Yes

Filling port: Yes

**Drain Port:** Yes

Plug for Vacumeter: Option

Plug for the Manometer: Option

Material of casing: Cast iron

Material of impeller: Cast iron

Material of wear plate: Steel

Material of shaft: Stainless steel AISI316

Material of non-return valve: NBR (Nitrile)

Shaft sealing: YCV Mechanical Seal with Grease Lubrication in SiC/SiO<sub>2</sub>/FKM (Viton®) on Stainless Steel

Sleeve

#### **Drive**

Type of drive unit: Three-Phase Electric Motor

**Drive Manufacturer: WEG** 

Efficiency class: IE3

Rated Power:  $1,\,1\,\text{kW}$ 

Maximal Rotation: 2900 rpm (50 Hz)

Rated voltage:  $400 \text{ V} \pm 10\% \otimes 50 \text{ Hz}$ ,  $230 \text{ V} \pm 10\% \otimes 50 \text{ Hz}$ 

Protection: 4 Amp (380-480 V), 6 Amp (220-277 V)

Mounting: B5

Frame: IEC 80

Cooling method: IC411- TEFC

Protection degree: IP55

Insulation class: F

#### **Performance data**

Typical application: waste water with solids in suspension, non-corrosive

Product temperature: max. 90 °C

Ambient temperature: max. 40 °C

Density: up to 1, 1 kg/dm³, for higher values you need an oversized motor

Viscosity: up to 30 mm<sup>2</sup>s (cSt), for higher values you need an oversized motor

Max vacuum with water: max 8 m (9, 5 m for 10 min)

Max vacuum with air: max 6 m

#### **Additional Features**

Setup position: Horizontal

Coupling: coupling integrated in the bracket

Paint: RAL6011 Reseda green



Net Weight: 38 kg

# **Product gallery:**



