





### **Product codes:**

Reference: 13427.41

## **Product short description:**

3" Self-priming centrifugal pump in cast iron with mechanical seal, grease-lubricated, non return valve and 7,5 kW electric motor Bi-Block (B5 standard motor flange-mounted on the pump bearing bracket)

+PS automatic lubricator for mechanical seal

## **Product features:**

## **Main Features**

Pump series: S 91

Pump Flow Rate: max 110 m<sup>3</sup>/h (1800 l/min)

Pump head with 50 Hz grid frequency:  $\max 24 \text{ m}$ 

Max. Solids Handling: 35 mm

Self-priming: ★★★☆

Heavy-duty: ★★★★

Construction: Bi-Block

### **Pump**

Type of Pump: Self-priming centrifugal pump

Suction port: 3"

Discharge port: 3"

Type of ports: Female Thread BSP

Type of self-priming: Wet-prime

Plug for Vacumeter: Option

Plug for the Manometer: Option



Material of casing: Cast iron

Material of impeller: Ductile Cast-iron

Material of wear plate: Steel

Material of shaft: Stainless steel AISI420

Material of non-return valve: NBR

Shaft sealing: YCV Mechanical Seal with Grease Lubrication in SiC/SiO<sub>2</sub>/FKM (Viton®) on Stainless Steel

Sleeve

#### Drive

Type of drive unit: Three-Phase Electric Motor

**Drive Manufacturer: WEG** 

Efficiency class: IE3

Rated Power: 7, 5 kW (10 HP)

Maximal Rotation: 1450 rpm (50 Hz)

Rated voltage:  $400 \text{ V} \pm 10\% \otimes 50 \text{ Hz}$ ,  $690 \text{ V} \pm 10\% \otimes 50 \text{ Hz}$ 

**Protection:** 16 Amp (380-480 V), 11 Amp (660-725 V)

Mounting: B5

Cooling method: IC411- TEFC

Protection degree: IP55

Insulation class: F

# **Performance data**

Typical application: waste water with solids in suspension, non-corrosive

Product temperature: max. 90 °C

Ambient temperature: max. 40 °C

Density: up to 1, 1 kg/dm³, for higher values you need an oversized motor

Viscosity: up to 5 mm<sup>2</sup>s (cSt), for higher values you need an oversized motor

Max vacuum with water: max 8 m (9, 5 m for 10 min)

Max vacuum with air: max 7, 5 m

### **Additional Features**

Setup position: Horizontal

Coupling: elastic coupling integrated in the bearing-house

Paint: RAL6011 Reseda green

External Dimensions (L x W x H): see dimensions

Net Weight: see dimensions

## **Product gallery:**





