



S 50 G31B+PS/T

Product codes:

Reference: 1390.41

Product short description:

2" Self-priming centrifugal pump in cast iron with mechanical seal, grease-lubricated, non return valve and 2,2 kW electric motor, on baseplate with coupling and guard.

+PS automatic lubricator for mechanical seal

Product features:

Main Features

Pump series: S 50

Pump Flow Rate: max 40 m³/h (655 l/min)

Pump head with 50 Hz grid frequency: $\max 15 \text{ m}$

Max. Solids Handling: 25 mm

Self-priming: ★★★☆☆

Heavy-duty: ★★★★

Construction: Classic

Pump

Type of Pump: Self-priming centrifugal pump

Pump manufacturer: Victor Pumps

Suction port: 2"

Discharge port: 2"

Type of ports: Female Thread BSP

Type of self-priming: Wet-prime

Inspection cover for the impeller: Yes



Filling port: Yes

Drain Port: Yes

Plug for Vacumeter: Option

Plug for the Manometer: Option

Material of casing: Cast iron

Material of impeller: Cast iron

Material of wear plate: Steel

Material of shaft: Stainless steel AISI316

Material of non-return valve: NBR (Nitrile)

Shaft sealing: YCV Mechanical Seal with Grease Lubrication in SiC/SiO₂/FKM (Viton®) on Stainless Steel

Sleeve

Drive

Type of drive unit: Three-Phase Electric Motor

Drive Manufacturer: WEG

Efficiency class: IE3

Rated Power: 2, 2 kW

Maximal Rotation: 2900 rpm (50 Hz)

Rated voltage: 400 V $\pm 10\%$ @ 50 Hz, 230 V $\pm 10\%$ @ 50 Hz

Protection: 7 Amp (380-480 V), 10 Amp (220-277 V)

Mounting: B3

Frame: IEC 90

Cooling method: IC411- TEFC

Protection degree: IP55

Insulation class: F

Performance data

Typical application: waste water with solids in suspension, non-corrosive

Product temperature: max. 90 °C

Ambient temperature: max. 40 °C

Density: up to 1, 1 kg/dm³, for higher values you need an oversized motor

Viscosity: up to 30 mm²s (cSt), for higher values you need an oversized motor

Max vacuum with water: max 8 m (9, 5 m for 10 min)

Max vacuum with air: max 7, 5 m

Additional Features

Setup position: Horizontal

Coupling: Elastic coupling with steel coupling guard

Arrangement: Steel base plate

Paint: RAL6011 Reseda green

External Dimensions (L x W x H): see dimensions



Product gallery:



