




S 80+60 G31T+PS



Product codes:

Reference: 13370.01

Product short description:

3" Self-priming centrifugal pump in cast iron with mechanical seal, grease-lubricated, non return valve and 5,5 kW electric motor close coupled
+PS automatic lubricator for mechanical seal

Product features:


Main Features
Pump series: S 80+60
Pump Flow Rate: max 83 m ³ /h (1383 l/min)
Pump head with 50 Hz grid frequency: max 24 m
Max. Solids Handling: 32 mm
Self-priming: ★★☆☆☆
Heavy-duty: ★★★★★
Construction: Close Coupled
Pump
Type of Pump: Self-priming centrifugal pump
Suction port: 3"
Discharge port: 3"
Type of ports: Female Thread BSP
Type of self-priming: Wet-prime
Inspection cover for the impeller: Yes
Filling port: Yes





Drain Port: Yes
Plug for Vacuometer: Option
Plug for the Manometer: Option
Material of casing: Cast iron
Material of impeller: Cast iron
Material of wear plate: Steel
Material of shaft: Stainless steel AISI316
Material of non-return valve: NBR (Nitrile)
Shaft sealing: YCV Mechanical Seal with Grease Lubrication in SiC/SiO ₂ /FKM (Viton®) on Stainless Steel Sleeve
Drive
Type of drive unit: Three-Phase Electric Motor
Drive Manufacturer: Victor Pumps
Efficiency class: IE3
Rated Power: 5, 5 kW
Maximal Rotation: 2900 rpm (50 Hz)
Rated voltage: 400 V $\pm 10\%$ @ 50 Hz, 690 V $\pm 10\%$ @ 50 Hz
Protection: 15 Amp (380-480 V), 8 Amp (220-277 V)
Cooling method: IC411- TEFC
Protection degree: IP55
Insulation class: F
Performance data
Typical application: waste water with solids in suspension, non-corrosive
Product temperature: max. 60 °C
Ambient temperature: max. 40 °C
Density: up to 1, 1 kg/dm ³ , for higher values you need an oversized motor
Viscosity: up to 20 mm ² s (cSt), for higher values you need an oversized motor
Max vacuum with water: max 8 m (9, 5 m for 10 min)
Max vacuum with air: max 7, 5 m
Additional Features
Setup position: Horizontal
Coupling: One shaft solution without any coupling
Paint: RAL6011 Reseda green
External Dimensions (L x W x H): see dimensions
Net Weight: see dimensions

Product gallery:

8:00 T-52


$$\begin{aligned} \log &= 21 \\ \sigma^2 &= 0.78 \end{aligned}$$


kg = 85






www.elsevier.com/locate/jmb

S 80+60 - 50 Hz

LEIFSD
Impeller @ CMV
Chassis

Fastenoffs bei
Stützpunkt 2: 21.10.2011

Umlaufzeit
Speed – 2000 min.
Verzögerung



www.waterpumps.com