


S161 G31B+PS/T



#### **Product codes:**

Reference: 3493.141

## **Product short description:**

6" Self-priming centrifugal pump in cast iron with mechanical seal, grease-lubricated, non return valve and 18,5 kW electric motor, on baseplate with coupling and guard.

+PS automatic lubricator for mechanical seal

## **Product features:**

## **Main Features**

Pump series: S161

Pump Flow Rate: max 340 m<sup>3</sup>/h (5667 l/min)

Pump head with 50 Hz grid frequency:  $max\ 20\ m$ 

Max. Solids Handling: 54 mm

Self-priming: ★★★☆

Heavy-duty:  $\star\star\star\star$ 

Construction: Classic

#### **Pump**

Type of Pump: Self-priming centrifugal pump

Suction port: 6"

Discharge port: 6"

Type of ports: Counter flanges to weld

Inspection cover for the impeller: Yes

Filling port: Yes

**Drain Port:** Yes



Plug for Vacumeter: Option

Plug for the Manometer: Option

Material of casing: Cast iron

Material of impeller: Ductile Cast-iron

Material of wear plate: Ductile Cast-iron

Material of shaft: Stainless steel AISI420

Material of non-return valve: NBR (Nitrile)

Shaft sealing: YCV Mechanical Seal with Grease Lubrication in SiC/SiO<sub>2</sub>/FKM (Viton®) on Stainless Steel

Sleeve

#### Drive

Type of drive unit: Three-Phase Electric Motor

Drive Manufacturer: WEG

Efficiency class: IE3

Rated Power: 18, 5 kW

Maximal Rotation: 1450 rpm (50 Hz)

Rated voltage: 400 V ±10% @ 50 Hz, 690 V ±10% @ 50 Hz

Protection: 45 Amp (380-480 V), 26 Amp (660-725 V)

Mounting: B3

Frame: IEC 180M

Cooling method: IC411- TEFC

Protection degree: IP55

Insulation class: F

#### **Performance data**

Typical application: waste water with solids in suspension, non-corrosive

Product temperature: max. 90 °C

Ambient temperature: max. 40 °C

Density: up to 1, 3 kg/dm³, for higher values you need an oversized motor

Viscosity: up to 30 mm<sup>2</sup>s (cSt), for higher values you need an oversized motor

Max vacuum with water: max 8 m (9, 5 m for 10 min)

Max vacuum with air: max 6 m

#### **Additional Features**

Setup position: Horizontal

Coupling: Elastic coupling with steel coupling guard

Arrangement: Steel base plate

Paint: RAL6011 Reseda green

External Dimensions (L x W x H): see dimensions

Net Weight: see dimensions



# **Product gallery:**

