


S180+50 G31B+PS/T



Product codes:

Reference: 35524.41

Product short description:

6" Self-priming centrifugal pump in cast iron with mechanical seal, grease-lubricated, non return valve and 30 kW electric motor, on baseplate with coupling and guard.

+PS automatic lubricator for mechanical seal

Product features:

Main Features

Pump series: S180+50

Pump Flow Rate: max 340 m³/h (5667 l/min)

Pump head with 50 Hz grid frequency: $max\ 20\ m$

Max. Solids Handling: 54 mm

Self-priming: ★★★★

Heavy-duty: ★★★☆☆

Construction: Classic

Pump

Type of Pump: Self-priming centrifugal pump

Suction port: 6"

Discharge port: 6"

Type of ports: Counter flanges to weld

Inspection cover for the impeller: Yes

Filling port: Yes

Drain Port: Yes



Plug for Vacumeter: Option

Plug for the Manometer: Option

Material of casing: Cast iron

Material of impeller: Ductile Cast-iron

Material of wear plate: Steel

Material of shaft: Stainless steel AISI420

Material of non-return valve: NBR (Nitrile)

Shaft sealing: YCV Mechanical Seal with Grease Lubrication in SiC/SiO₂/FKM (Viton®) on Stainless Steel

Sleeve AISI420

Drive

Type of drive unit: Three-Phase Electric Motor

Drive Manufacturer: WEG

Efficiency class: IE3

Rated Power: 30 kW

Maximal Rotation: 1450 rpm (50 Hz)

Rated voltage: $400 \text{ V} \pm 10\% \otimes 50 \text{ Hz}$, $690 \text{ V} \pm 10\% \otimes 50 \text{ Hz}$

Protection: 64 Amp (380-480 V), 37 Amp (660-725 V)

Mounting: B3

Frame: IEC 200L

Cooling method: IC411- TEFC

Protection degree: IP55

Insulation class: F

Performance data

Typical application: waste water with solids in suspension, non-corrosive

Product temperature: max. 90 °C

Ambient temperature: max. 40 °C

Density: up to 1, 1 kg/dm³, for higher values you need an oversized motor

Viscosity: up to 20 mm²s (cSt), for higher values you need an oversized motor

Max vacuum with water: max 8 m (9, 5 m for 10 min)

Max vacuum with air: max 6 m

Additional Features

Setup position: Horizontal

Coupling: Elastic coupling with steel coupling guard

Arrangement: Steel base plate

Paint: RAL6011 Reseda green

External Dimensions (L x W x H): see dimensions

Net Weight: see dimensions



Product gallery:

