



S 60+50 G31RZ+T

Product codes:

Reference: X26637

Product short description:

2" Self-priming centrifugal pump in cast iron with mechanical seal, grease-lubricated, non return valve and Diesel engine, mounted on trolley with lifting hook and rubber wheels.

Product features:

Main Features

Pump series: 560+50

Pump Flow Rate: max 50 m³/h (830 l/min)

Pump head with 50 Hz grid frequency: max 57 m

Max. Solids Handling: 24 mm

Self-priming: ★★★☆

Heavy-duty: ★★★☆☆

Construction: Mobile Pumps

Frame: Single-axle trolley

Suitable for the EU sales area: Yes

Suitable for the US sales area: No

Suitable for non regulated sales areas: Yes

Frame

Type of Tyre: Solid rubber wheels with tractor profile

Suitable for solid ground: Yes

Suitable for muddy and sandy terrains: Yes



Lifting hook: Yes

Can be moved by hand: Yes

Can be towed with a vehicle: No

Towing bar with hook: No

Document box prepared for lock: NO

Tool box prepared for lock: No

Tank on engine: Yes

Tank integrated in frame: No

Tank Capacity: 5 |

Pump

Type of Pump: Self-priming centrifugal pump

Pump manufacturer: Victor Pumps

Suction port: 2"

Discharge port: 2"

Type of ports: Female Thread BSP

Type of self-priming: Wet-prime

Vaccum pump: No

Inspection cover for the impeller: Yes

Filling port: Yes

Drain Port: Yes

Plug for Vacumeter: Option

Plug for the Manometer: Option

Material of casing: Cast iron

Material of impeller: Cast iron

Material of wear plate: Steel

Material of shaft: Stainless steel AISI316

Material of non-return valve: NBR (Nitrile)

Shaft sealing: YCV Mechanical Seal with Grease Lubrication in SiC/SiO₂/FKM (Viton®) on Stainless Steel

Sleeve

Drive

Type of drive unit: Diesel

Drive Manufacturer: Hatz

Drive code: 1B40

Manual Start: Yes

Electric start: No

Strokes: 4-stroke

Displacement: 462 cm³

Rated Power: 7, 3 kW (9, 8 HP)

Maximal Rotation: 3600 rpm



Cooling: Air cooled

Performance data

Typical application: waste water with solids in suspension, non-corrosive

Product temperature: max. 60 °C

Ambient temperature: max. 40 °C

Density: up to 1, 1 kg/dm³, for higher values you need an oversized motor

Viscosity: up to 1 mm²s (cSt), for higher values you need an oversized motor

Max vacuum with water: max 8 m (9, 5 m for 10 min)

Max vacuum with air: max 8, 5 m

Additional Features

Paint: RAL1006 maize yellow

External Dimensions (L x W x H): see dimensions

Net Weight: see dimensions

Product gallery:



