



S161 G31T+TQ

Product codes:

Reference: X23747



Product short description:

6" Self-priming centrifugal pump in cast iron with mechanical seal, grease-lubricated, non return valve and 18,5 kW electric motor close coupled, mounted on trailer with towing eye, lifting hook and tyres.

Product features:

Main Features
Pump series: S161
Pump Flow Rate: max 350 m³/h (5833 l/min)
Pump head with 50 Hz grid frequency: max 20 m
Max. Solids Handling: 54 mm
Self-priming: ★★★★★
Heavy-duty: ★★★★★
Construction: Mobile Pumps
Frame: Single-axle Trailer
Frame
Type of Tyre: 10" Tyres with Tractor Profile
Suitable for solid ground: Yes
Suitable for muddy and sandy terrains: Yes
Lifting hook: Yes
Can be moved by hand: Yes
Can be towed with a vehicle: Yes



Towing bar with hook: Yes
Pump
Type of Pump: Self-priming centrifugal pump
Pump manufacturer: Victor Pumps
Suction port: 6"
Discharge port: 6"
Type of ports: Counter flanges to weld
Type of self-priming: Wet-prime
Vaccum pump: No
Inspection cover for the impeller: Yes
Filling port: Yes
Drain Port: Yes
Plug for Vacuometer: Yes
Plug for the Manometer: Option
Material of casing: Cast iron
Material of impeller: Ductile Cast-iron
Material of wear plate: Steel
Material of shaft: Stainless steel AISI304
Material of non-return valve: NBR (Nitrile)
Shaft sealing: YCV Mechanical Seal with Grease Lubrication in SiC/SiO ₂ /FKM (Viton®) on Stainless Steel
Sleeve
Drive
Type of drive unit: Three-Phase Electric Motor
Drive Manufacturer: Victor Pumps
Efficiency class: IE1, S6-75%
Rated Power: 18, 5 kW
Maximal Rotation: 1450 rpm (50 Hz)
Rated voltage: 400 V ±10% @ 50 Hz, 690 V ±10% @ 50 Hz
Protection: 45 Amp (380-480 V), 26 Amp (660-725 V)
Cooling method: IC411- TEFC
Protection degree: IP55
Insulation class: F
Performance data
Typical application: waste water with solids in suspension, non-corrosive
Product temperature: max. 60 °C
Ambient temperature: max. 40 °C
Density: up to 1, 1 kg/dm ³ , for higher values you need an oversized motor
Viscosity: up to 30 mm ² s (cSt), for higher values you need an oversized motor

Max vacuum with air: max 7, 5 m

Additional Features

Coupling: One shaft solution without any coupling

Plug: IEC 64 Amp, 5 Pin with Phase inversion

Paint: RAL1006 maize yellow

External Dimensions (L x W x H): see dimensions

Net Weight: see dimensions

Product gallery:



